



# FS-1110

Monochrome Laser Printer for A4 Size



## A PRINTER TO FORM A PARTNERSHIP WITH

This efficient printer is so reliable that you can install it and simply forget about it. A pure desktop device that takes a mere 6 seconds to output the first page, you can trust it to deliver high quality printing without interruption. No matter how busy you are, you can rely on the FS-1110 to get things done.

- >> Up to 25 pages per minute with true 1,200 dpi resolution
- >> Standard Paper Tray of 250 sheets with Multi-purpose Tray for custom size printing.
- >> Compact design, robust and reliable
- >> Powerful controller with 32MB RAM as standard
- >> Long-life components



**ECO N O M Y**  
**ECO nomy**  
Lower running costs



**ECO L O G Y**  
**ECOlogy**  
Long-life components



**SYS TEM**  
**SYStem Printing**  
Modularity, upgradability, and functionality

# Flexibility, reliability and efficiency for today and tomorrow.

## FS-1110



FS-1110 paper tray



FS-1110 Printer offers output tray for multiple output prints.



LED control panel makes operation easy



FS-1110 Toner cartridge

For many business, the need for a fast, reliable and productive desktop laser printer is important for Creating everyday business documents. This compact, yet fast desktop monochrome laser printer Provides users with up to 25 page per minute and connects easily to any PC with a standard USB Interface. With its strong productivity and low cost of ownership thanks to Kyocera's ECOSYS long life Technology, the FS-1110 is the desktop printer you can count on.



### Basic Specifications

General Type	Monochrome A4 Desktop Printer
Technology	KYOCERA ECOSYS Black & White Laser Printers
Engine Speed in Pages Per Minute	Up to 24 pages per minute in A4 ; Letter size printing 25ppm.
Warm-up Time	Approx. 19/14 seconds or less from power on
First Copy / Print Out Time	Approx. 9 seconds or less ( Eco User Off)
Resolution	Fast 1200 Mode, 600x600 dpi, 300x300 dpi
Standard Memory	Standard 32MB RAM
Duplex Printing	Manual
Dimensions (W x D x H)	Main unit: 375 mm x 393 mm x 250 mm
Weight	Main unit approx. 11kg ( Without toner)
Noise (ISO 7779 / ISO 9296)	Printing: 67 dB(A) :: Stand-by: 30 dB(A)
Power Consumption	Printing: 417 W, Stand-by: 8W, further goes down in Sleep mode.
Power Source	AC 220 ~ 240 V, 50/60 Hz
Max Monthly Duty Cycle	Max. 10,000 pages per month : Max. average 500 -2500pages per month
Manufacturing Standard	This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

### Controller Specifications

Processing Unit /Mhz	IBMPower PC 405F5 360Mhz
Support Client Operating Systems	Certified for Microsoft® Windows Vista® 32/64-bit, Windows® 2000, Windows XP® Mac OS X Version, UNIX, LINUX as well as other operating system on request.
Connectivity / Interfaces	High Speed USB 2.0 Host
Additional Print Features	N-Up Printing, EcoPrint Mode, Poster Mode.

### Paper Supply

Standard Paper Sources	250 Sheet Drawer, 1 Sheet Multi-Purpose Tray
Multi-Purpose Tray Paper	Letter, Legal, A4, B5, A5, Folio, Oficio 2, Statement, Executive, A6, B6, B5, Envelope, Monarch
Input capacity	250-sheet universal paper cassette, 60-120 g/m <sup>2</sup> , A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm to 215.9 x 297 mm) 1-sheet manual feed, 60-220 g/m <sup>2</sup> , A4, A5, A6, B5, Letter, Custom (70 x 148 mm to 215.9 x 356 mm)
Input Materials	Plain, Preprinted, Bond, Recycled, Rough, Letterhead, Color, Pre-Punched, High Quality, Transparency, Labels, Bond, Vellum, Envelope, Cardstock, Thick Paper, Custom
Output Capacity	250 sheets A4 face down
General paper handling	All paper capacities quoted are based on a paper weight of 80 g/m <sup>2</sup> . Please use paper recommended by KYOCERA under normal environmental conditions.

### Others

Storage (I/F)	CF ( For Firm update) - 1 slot for CF Card Type
---------------	---

### Interfaces

Standard interface	USB 2.0 (Hi-Speed)
--------------------	--------------------

### Consumables

TK-1104 Toner kit	Standard Black Toner for 2100 pages (shipped with 1000 pages) in accordance with ISO/IEC 19572
Photo conductor unit	Standard life of 1,00,000 prints *

### Others Options

External Network unit	External Print server unit, 10 Base - T / 100 Base - TX
	The ports available on board are USB port, and RJ-45 Ports.

Disclaimer: Specifications and external appearances are subject to change without prior notice.



**KYOCERA MITA India Pvt. Ltd.**

First Floor, Orchid Centre, Sector-53, Golf Course Road,

Gurgaon - 122002 (Haryana), India

Tel: +91-124-4671000, Fax: +91-124-4671001

email: contactus@kyoceramita.co.in

www.kyoceramita.co.in

